



MSDS

MATERIAL SAFETY DATA SHEET

PRODUCT TRADE NAME:

HOMAX PRODUCTS, INC.
OOPS! PREP-A-WALL
ITEM #710824

HAZARDOUS MATERIAL INFORMATION SYSTEM

HEALTH	1
--------	---

FLAMMABILITY	1
--------------	---

REACTIVITY	0
------------	---

(HAZARD RATING: 0=LEAST, 1=SLIGHT, 2=MODERATE, 3=HIGH, 4=EXTREME) (I=SAFETY GLASSES, GLOVES, VAPOR RESPIRATOR)

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME:
HOMAX PRODUCTS, INC.
468 W. HORTON ROAD
BELLINGHAM WA 98226

24 HOUR EMERGENCY PHONE NUMBER:
CHEMTREC 1-800-424-9300
INFORMATION PHONE NUMBER: 1-800-729-9029
DATE OF PREPARATION: 01/15/03

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

CAS NUMBER	DESCRIPTION	PEL	TLV	%
1. 123-42-2	DIACETONE ALCOHOL	50PPM	50PPM	<7%
2. 872-50-4	2-PYRROLIDINONE, 1-METHYL	NONE	NONE	<5%
3. 111-76-2	2-BUTOXYETHANOL	NONE	NONE	<81%
	WATER			

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

APPEARANCE AND ODOR:	THIN COLORED LIQUID /SOLVENT WITH DISTINCTIVE ODOR.
BOILING RANGE:	340 DEGREES F (REPRESENTS LOWEST BOILING POINT OF INDIVIDUAL RAW MATERIALS)
MELTING POINT:	N/A
VAPOR PRESSURE (MMHG/70F):	<0.95 MMHG @ 20C
WATER SOLUBILITY %:	COMPLETE
VAPOR DENSITY (AIR = 1):	> 1
EVAPORATION RATE:	>0.12 (BUTYL ACETATE = 1.0)
SPECIFIC GRAVITY (WATER = 1)	0.9926-8.09 POUNDS PER GALLON

N/E = NOT ESTABLISHED

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: > 200 F TAG CLOSED CUP
LEL: N/A
FLAMMABLE LIMITS: N/A
UEL: N/A
EXTINGUISHING MEDIA: WATER FOG, FOAM, DRY CHEMICAL OR CARBON DIOXIDE.

SPECIAL FIREFIGHTING PROCEDURES:
DO NOT USE DIRECT STREAM OF WATER ON POOL FIRES.

PROTECTIVE EQUIPMENT:
APPROVED SELF-CONTAINED BREATHING APPARATUS & FULL BUNKER GEAR SHOULD BE WORN.

UNUSUAL FIRE & EXPLOSION HAZARDS:
KEEP CONTAINERS COOL WITH WATER. PRESSURE BUILD UP COULD RESULT IN CONTAINER RUPTURE.
VAPOR IS HEAVIER THAN AIR.

SECTION V - REACTIVITY DATA

STABILITY:
STABLE

CONDITIONS TO AVOID:
HEAT; HOT SURFACES AND ALL SOURCES OF IGNITION.

INCOMPATIBILITY (MATERIALS TO AVOID):
CHLORINATED COMPOUNDS AND OXIDIZING MATERIALS. ACIDS, ALKALIES.

HAZARDOUS DECOMPOSITION PRODUCTS:
SULFUR DIOXIDE, CARBON DIOXIDE, CARBON MONOXIDE AND UNIDENTIFIED ORGANICS MAY BE FORMED DURING COMBUSTION.

HAZARDOUS POLYMERIZATION:
WILL NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

INHALATION:
VAPORS MAY CAUSE IRRITATION TO THE NOSE, THROAT AND RESPIRATORY TRACT.

INGESTION:
SORE THOAT, ABDOMINAL PAIN, NAUSEA, VOMITING AND DIARRHEA.

EYES:
IRRITATION INCLUDING PAIN, TEARING, REDDENING AND SWELLING.

SKIN:
REDDENING, SWELLING, RASH AND REDNESS.

CHRONIC:
MAY CAUSE INJURY TO KIDNEYS AND LIVER. PROLONGED OR REPEATED OVER EXPOSURE TO SKIN
MAY CAUSE DRYING, DEFATTING, AND DERMATITIS.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION:
REMOVE TO AREA FREE OF VAPORS AND SUPPORT/RESTORE BREATHING. SEEK MEDICAL ATTENTION IMMEDIATELY.

EYES:

FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION IMMEDIATELY.

INGESTION:

DO NOT GIVE LIQUIDS IF VICTIM IS VERY DROWSY. OTHERWISE, GIVE 1-2 GLASSES OF WATER AND INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. SEEK MEDICAL ATTENTION IMMEDIATELY.

SKIN:

REMOVE CONTAMINATED CLOTHING AND WASH AFFECTED AREA WITH SOAP AND WATER. DO NOT REUSE CONTAMINATED ARTICLES. SEEK MEDICAL ATTENTION IMMEDIATELY.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

FOR LARGE SPILLS EVACUATE THE HAZARD AREA OF UNPROTECTED PERSONNEL. WEAR APPROPRIATE RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF SOURCE OF LEAK ONLY IF SAFE TO DO SO. DIKE AND CONTAIN. IF VAPOR CLOUD FORMS, WATER FOG MAY BE USED TO SUPPRESS; CONTAIN RUN-OFF. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSELS. SOAK UP RESIDUE WITH AN ABSORBENT SUCH AS CLAY, SAND OR OTHER SUITABLE MATERIAL; PLACE IN NONLEAKING CONTAINERS FOR PROPER DISPOSAL. SEAL TIGHTLY FOR PROPER DISPOSAL.

NEUTRALIZING AGENT: N/A

WASTE DISPOSAL:

DO NOT FLUSH INTO SEWERS OR WATERWAYS. DISPOSE OF IN ACCORDANCE WITH LOCAL, COUNTY, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS FOR SAFE HANDLING & USE:

STORE IN COOL, DRY PLACE. AWAY FROM SOURCES OF IGNITION. USE AND STORE WITH ADEQUATE VENTILATION IN PROPERLY LABELED, CLOSED CONTAINERS. AVOID INHALATION OF VAPORS AND SKIN CONTACT. DO NOT TAKE INTERNALLY. DISPOSAL CONTAINERS MUST BE SEALED TIGHTLY AND PROPERLY LABELED. DO NOT EAT, DRINK OR SMOKE IN WORK AREA. WASH HANDS THOROUGHLY AFTER USE.

OTHER PRECAUTIONS:

N/A

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION:

IF EXPOSURE EXCEEDS TLV, USE NIOSH APPROVED RESPIRATOR.

VENTILATION:

USE EXPLOSION-PROOF VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS.

PROTECTIVE GLOVES:

CHEMICAL RESISTANT

EYE PROTECTIONS:

SPLASHPROOF GOGGLES.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

SAFETY SHOWERS AND EYE WASH STATIONS SHOULD BE AVAILABLE FOR USE IN AN EMERGENCY.

WORK/HYGIENIC PRACTICES:

WASH HANDS THOROUGHLY AFTER USE, BEFORE DRINKING, EATING OR SMOKING.

SUPPLIER SAFETY & HEALTH DATA:

N/A

SECTION IX – TRANSPORTATION DATA/DISCLAIMER

HAZARD CLASS: NOT REGULATED

DOT SHIPPING NAME: N/A

UN NUMBER: N/A

NA # : N/A

OTHER: THE ORM-D CLASSIFICATION APPLIES TO CONTAINERS UNDER ONE GALLON IN SIZE AND IS NOT APPLICABLE TO AIR SHIPMENT.

THE INFORMATION IN THIS DOCUMENT IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THE PRODUCT, OR THE HAZARDS RELATED TO ITS USE. THIS INFORMATION AND PRODUCT ARE FURNISHED ON THE CONDITION THAT THE PERSON RECEIVING THEM SHALL MAKE HIS OWN DETERMINATION AS TO THE SUITABILITY OF THE PRODUCT FOR HIS PARTICULAR PURPOSE AND ON THE CONDITION HE ASSUMES THE RISK OF HIS USE THEREOF.